




Color: White

Weight: 9.5 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant Current
120V	0.33A/0.29A/0.25A
208V	0.19A/0.17A/0.14A
240V	0.17A/0.15A/0.13A
277V	0.14A/0.13A/0.11A
Input Watts	29.73-39.96W

LED Info

Watts	40/35/30W
Color Temp	3500/4000/5000K
Color Accuracy	84-85 CRI
L70 Lifespan	100,000 Hours
Lumens	4,140-5,509 lm
Efficacy	130.3-145 lm/W

Technical Specifications

Field Adjustability

Field Adjustable:

Field Adjustable Light Output:
40/35/30W (factory default 40W)
Color temperature selectable 3500K, 4000K and
5000K (factory default 4000K)

Compliance

UL Listed:

Suitable for wet locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been
tested by an independent laboratory in accordance
with IESNA LM-79 and LM-80.

IC Rated:

Suitable for direct contact with insulation

CCEA Compliant:

Luminaire Requirements used in Environmental Air
Space per the electrical code specification of the City
of Chicago

DLC Listed:

This product family is listed with the DesignLights
Consortium (DLC). Individual SKUs within this family
may carry either a DLC Standard or DLC Premium
qualification. Please refer to the individual product
specification sheet or the DLC Qualified Products List
(QPL) at designlights.org to confirm the qualification
status of a specific SKU prior to specification or
purchase.

Electrical

Driver:

40W: Constant Current, Isolated/Class 2, 120-277V,
50/60 Hz, 120V: 0.33A, 208V: 0.19A, 240V: 0.17A,
277V: 0.14A
35W: Constant Current, Isolated/Class 2, 120-277V,
50/60 Hz, 120V: 0.29A, 208V: 0.17A, 240V: 0.15A,
277V: 0.13A
30W: Constant Current, Isolated/Class 2, 120-277V,
50/60 Hz, 120V: 0.25A, 208V: 0.14A, 240V: 0.13A,
277V: 0.11A

Dimming Driver:

Driver includes dimming control wiring for 0-10V
dimming systems. Requires separate 0-10V DC
dimming circuit. Dims down to 10%.

THD:

6.22% at 120V, 4.49% at 277V

Power Factor:

99.6% at 120V, 96.4% at 277V

Aux Power Supply:

Yes

Dim to Off:

Yes

Surge Protection:

L-N:2.5 kV,L/N-GND:2.5 kV

Battery Backup:

Battery backup will operate the LED Lamp for 90
minutes if power fails. Wired for 120V-277V.

Battery Backup Light Loss Factor:

40W: 0.20
35W: 0.23
30W: 0.27

Construction

Cold Weather Starting:

The minimum starting temperature is -40°F (-40°C)

Maximum Ambient Temperature:

Suitable for use in up to 104°F (40°C)

Housing:

Sheet metal

Technical Specifications (continued)

Lens:

Polycarbonate lens

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Installation**Mounting:**

Recessed into T-grid ceiling. Surface and recessed mounting kits available for drywall ceilings.

LED Characteristics**LEDs:**

Long-life, high-efficacy, surface-mount LEDs

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance**Lifespan:**

100,000-Hour LED lifespan based on IESlm-80 results and TM-21 calculations

Lightcloud**Wireless Network Lighting Control:**

Control any fixture in your Lightcloud integrated/embedded networked lighting luminaire-level control system. LLLC - capable of switching, 0-10V dimming, power/energy monitoring. Can also be used to extend the range of the Lightcloud mesh network communication protocols.

DLC system - Interior: N1XMLOEATBA; Exterior: NHCZ2BIA17L

Learn more at www.lightcloud.com

Gateway Required:

Yes

Communication Protocol:

Cellular/Zigbee Mesh

Range:

100 ft through obstructions; up to 1,000 feet clear line of sight

Spacing Criteria:

Lightcloud devices should be placed within the specified range to communicate within the mesh network.


Sensor Settings**Occupied Actions:**

On or On at a Dim Level

Other**5-Year Limited Warranty:**

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- 100,000-Hour LED lifespan
- DLC Premium Listed
- 5-Year, limited warranty

Ordering Matrix

Family		Length/Wattages	Color Temp	Finish	Driver	Options
SWISH34	-	2X4				/LC/E
		2X2 = 2' x 2' (30/25/18W) 2X4 = 2' x 4' (40/35/30W) 1X4 = 1' x 4' (30/25/18W)	Blank = 3500/4000/5000K CCT Adjustable	Blank = White	Blank = 120-277V, 0-10V Dimming	/LCBS/MVS/E = Lightcloud Blue w/MVS Sensor & Battery Backup /LCBS/E = Lightcloud Blue w/PIR Sensor & Battery Backup /PIR/E = Passive Infrared Occupancy Sensor w/Battery Backup /MVS/E = Microwave Occupancy Sensor w/Battery Backup /LC/E = Lightcloud w/Battery Backup /LCBS/MVS = Lightcloud Blue w/MVS Sensor /LCBS = Lightcloud Blue w/PIR Sensor /PIR = Passive Infrared Occupancy Sensor /MVS = Microwave Occupancy Sensor /LC = Lightcloud /E = Battery Backup Blank = No Option