


Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

Replacement for conventional fluorescent T8 and T12 linear tubes

Technical Specifications		
<p>Performance</p> <p>Product Type: Linear</p> <p>Input Wattage: 13W</p> <p>Lumens (Nominal): 2,000lm</p> <p>Efficacy: 133lm/W</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p> <p>Compliance</p> <p>UL Listed: Suitable for damp locations</p> <p>Enclosed Fixtures: Suitable for use in enclosed fixtures</p> <p>Model Number for Certification: T10331(T5HE-13-48P-840-EXT)</p>	<p>DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PLNR7W32YM5B</p> <p>LED Characteristics</p> <p>Color Temperature: 4000K</p> <p>Color Accuracy (CRI): ≥80 CRI</p> <p>Construction</p> <p>Bulb Shape: T5 4FT</p> <p>Base Type: G5</p> <p>Endcap Material: Plastic</p> <p>Enclosure Material: Polycarbonate and Aluminum</p>	<p>Optical</p> <p>Beam Angle: 145°</p> <p>Electrical</p> <p>THD: 20%</p> <p>Power Factor: 0.9</p> <p>Operating Temperature: -20°C to 45°C (-4°F to 113°F)</p> <p>Input Voltage: Driver Dependent</p> <p>Operating Frequency: 50/60Hz</p> <p>Dimming: Yes with 0-10V dimmer. See Dimmer Compatibility List.</p>

Technical Specifications (continued)

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
20	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	6.7	5.1	7
PALLET	48	48.82	40.16	40.94

Dimension

