

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



### Features and Benefits

- Replacement for conventional fluorescent tubes
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Double ended wiring method
- 50,000 hour Lifespan
- Rated for use in enclosed and open fixtures in dry or damp locations
- Diffused frosted lens will maintain the same light quality over time
- Instant on full brightness
- Environmentally friendly, no mercury used
- NSF Listed: NSF/ANSI Standard 2 - Food Equipment - Splash Zone (Not for Direct Food Zone without additional fixture considerations)
- UL Classified, DLC Listed
- Emergency back up available. Catalog Numbers: DRI-5-EMGR-T8, DRI-10-EMGR-TYPE B

Technical Specifications		
<b>Performance</b>	<b>Bulb Shape:</b>	<b>Input Voltage:</b>
<b>Product Type:</b> Linear	T5	120-277V AC
<b>Input Wattage:</b> 16W	<b>Nominal Length:</b> 3 ft SE	<b>Operating Frequency:</b> 50/60Hz
<b>Lumens (Nominal):</b> 2,050lm	<b>Base Type:</b> G5	<b>Input Current @ 120V:</b> 140mA
<b>Efficacy:</b> 128lm/W	<b>LED Characteristics</b>	<b>Optical</b>
<b>L70 Lifespan:</b> 50,000 Hours	<b>Color Temperature:</b> 3500K Neutral White	<b>Beam Angle:</b> 180°
<b>Wattage Equivalency:</b> 39W Fluorescent	<b>Electrical</b>	<b>Other</b>
<b>Construction</b>	<b>THD:</b> <20%	<b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a> .
<b>Material:</b> Metal	<b>Power Factor:</b> >0.9	<b>Compliance</b>
<b>Enclosure Material:</b> Glass	<b>Operating Temperature:</b> -20°C to 45°C (-4°F to 113°F)	<b>UL Recognized:</b> Yes
	<b>Dimming:</b> No	

## Technical Specifications (continued)

**UL Classified:**

Yes

**NSF Listed:**

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

**Application:**

Suitable for damp locations and totally enclosed fixtures.

### Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
36	0

### Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	36.36	5.28	25
PALLET	0	35.43	0.85	0.85

### Dimension

