



UPC: 192552045612

Color: White

Weight: 0.4 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type Constant Current
 120V N/A
 208V N/A
 240V N/A
 277V N/A
 Input Watts 12W

LED Info

Watts 12W
 Color Temp 3000/3500/4000/5000/6500K
 Color Accuracy 80 CRI
 L70 Lifespan 50,000 Hours
 Lumens 1,650 lm
 Efficacy 138

Technical Specifications**Performance****Product Type:**

Linear Tube

Description:

Hybrid Type A/B tubes allow installation on the ballast or direct wiring to line voltage. Now available with adjustable 5 CCT switch in clear or frosted lens.

Wattage Equivalency:

32W Fluorescent

Input Wattage:

12W

Nominal Lumens:

1,650lm

Electrical**THD:**

25%

Power Factor:

>0.9

Dimmable:

No

Input Voltage:

120-277V

Operating Frequency:

50/60Hz

Operating Temperature:

-4°F to 113°F (-20°C to 45°C)

Flicker:

<40%

LED Characteristics**Beam Angle:**

220°

Color Temperature:

Field adjustable via dip switch
 3000/3500/4000/5000/6500K

Color Accuracy (CRI):

80 CRI

R9 Value:

High color performance with R9 greater than 0

Color Consistency:

7-step MacAdam Ellipse binning to achieve
 consistent fixture-to-fixture color

Color Stability:

LED color temperature is warrantied to shift no more
 than 200K in color temperature over a 5-year period

Color Uniformity:

RAB's range of Correlated Color Temperature follows
 the guidelines of the American National Standard for
 Specifications for the Chromaticity of Solid State
 Lighting (SSL) Products, ANSI C78.377-2017.

Installation**Installation Method:**

UL Type A+B, Hybrid

Base Type:

G13

Construction**Length:**

4 ft

Shape:

T8

Finish:

White

Endcap Material:

Plastic

Enclosure Material:

Coated Glass

Lens Finish:

Frosted

Technical Specifications (continued)

Compliance

Listings:

UL Listed, UL Classified

Environment:

Suitable for use indoors in dry and damp environments.

Fixture Rating:

Suitable for use in enclosed fixtures

Energy Star Approved:

No

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

Certification Model Number:

T8-12-48GC-8CCT-HYB

California Title 20 Compliant:

No

California Title 24 JA8 Compliant:

No

California Energy Commission (CEC) Status:

Lawful for Sales in California

NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	50.67	6.19	7.05
PALLET	1	51.46	37.9	49.37

Dimension**Features**

Direct replacement for fluorescent lamps: F32T8/32W, F32T8/30W, F32T8/28W, F32T8/25W

TYPE A - Plug-and-play compatible with most common commercial T8 electronic ballasts

TYPE B - Can be wired directly to line voltage 120-277V. Can be wired using single- or double-ended method

Shatter resistant PET Coating makes these tubes perfect for demanding applications

5 color temperatures in 1 SKU (3000/3500/4000/5000/6500K)

Ordering Matrix

Family	Wattage	Length	Material	CRI/Color Temp	Driver	Wiring Method	Installation Method	Lens Finish
T8	12	48	GC	8CCT			HYB	
7.5 = 7.5W	24 = 2 ft	G = Glass	8CCT = 80 CRI, 3000/3500/4000/5000/6500K		Blank = 120-277V	Blank = Single + Double Ended	HYB = Hybrid	Blank = Frosted
10.5 = 10.5W	36 = 3 ft	GC = Glass Coated	CCT Adjustable					C = Clear
11 = 11W	48 = 4 ft							
12 = 12W								
15 = 15W								