

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

- LEDs located on both sides of the tube provides 360-degree light output
- Optics designed to deliver smooth even light without hot spots
- Multiple lengths available for any application needed
- 120V-277V - Universal voltage
- Ambient temperature: -20°C/-4°F to 55°C/131°F
- Rotatable endcaps allow installer to direct light where needed
- Robust plastic and aluminum construction to minimize breakage
- Mercury and UV free. RoHS-compliant components.
- Double-ended bypass installation for simple install and reduced maintenance costs

Technical Specifications		
<p>Performance</p> <p>Product Type: Linear</p> <p>Input Wattage: 26W</p> <p>Lumens (Nominal): 3,500lm</p> <p>Efficacy: 135lm/W</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations</p> <p>Wattage Equivalency: T8HO and T12HO</p> <p>LED Characteristics</p> <p>Color Accuracy (CRI): 80</p> <p>Color Temperature: 6500K</p>	<p>Electrical</p> <p>THD: <20%</p> <p>Power Factor: >0.9</p> <p>Dimmable: Non-Dim</p> <p>Operating Temperature: -20°C to 55°C</p> <p>Input Voltage: 120-277V</p> <p>Operating Frequency: 50/60Hz</p> <p>Construction</p> <p>Nominal Length: 64"</p> <p>Bulb Shape: T8</p>	<p>Enclosure Material: Plastic+Aluminum</p> <p>Lens Finish: Clear</p> <p>Base Type: R17D</p> <p>Optical</p> <p>Beam Angle: 360°</p> <p>Installation</p> <p>Installation Method: UL Type B, Ballast Bypass - Double Ended Wire</p> <p>Other</p> <p>Technology EQ: Fluorescent</p>

