

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Direct Replacement for Fluorescent Lamps: F32T8/32W, F32T8/30W, F32T8/28W, F32T8/25W
- Easy to install plug and play that requires no rewiring, no tools, no instructions
- 50,000 hour Lifespan
- Rated for use in enclosed and open fixtures in dry or damp locations
- Diffused frosted lens will maintain the same light quality over time
- Compatible with most instant start electronic T8 ballasts, see Ballast Compatibility List
- Approximately 40% more efficient than fluorescent T8 lamps
- Instant on full brightness
- Environmentally friendly, no mercury used
- NSF Listed: NSF/ANSI Standard 2 - Food Equipment - Splash Zone (Not for Direct Food Zone without additional fixture considerations)
- Dimmable, see Dimmer Compatibility List

Technical Specifications		
Performance	Color Accuracy (CRI):	Power Factor:
Product Type: Linear	≥80 CRI	0.9
Input Wattage: 9.5W	Construction	Operating Temperature: -20°C to 45°C (-4°F to 113°F)
Lumens (Nominal): 1,750lm	Bulb Shape: T8	Input Voltage: Ballast Dependent
Efficacy: 184lm/W	Base Type: G13	Operating Frequency: 50/60Hz
L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results	Nominal Length: 4 ft	Dimming: Yes with 0-10V dimmer & ballast. See Dimmer Compatibility List.
Compliance	Endcap Material: Polybutylene Terephthalate (PBT) & Copper	Other
UL Listed: Suitable for damp locations	Housing Material: Glass	Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .
Enclosed Fixtures: Suitable for use in enclosed fixtures	Optical	
LED Characteristics	Beam Angle: 160°	
Color Temperature: 5000K	Electrical	
	THD: 20%	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0.4	0.4	3
PALLET	1250	51.2	43.3	47.2

Dimension

