TICYN



Weight: 0.4 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Voltage
120V	N/A
208V	N/A
240V	N/A
277V	N/A
Input Watts	2.5 W/ftW

LED Info

Watts	2.5W/ftW
Color Temp	N/A
Color Accuracy	N/A
L70 Lifespan	50,000 Hours
Lumens	238lm/ft lm
Efficacy	95

Technical Specifications

Performance

Product Type:
32 ft No-Pixel COB tape static white - Damp rated

Description:
ARCTAPE is a flexible COB tape with a continuous band of flawless light output with no pixelated hot spots - even without a lens.

Input Wattage:
2.5W/ft

Lumens/Foot:
238 lm/ft

Efficacy:
95lm/W

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

LED Characteristics

Chip Density:
128 LED/ft

Beam Angle:
150°

Color Temperature:
3500K

Color Accuracy (CRI):
90 CRI

Color Changing:
No

R9 Value:
High color performance with R9 greater than 50

Color Consistency:
<3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Field Cuttable Increment:
Cuttable every 2"

LED Segments per Reel:
200

Electrical

Operating Temperature:
-20°C to 45°C (-4°F to 113°F)

Storage Temperature:
-4°F (-20°C) to 140°F(60°C)

Flicker:
Flicker Free - Pst LM<1, SVM<0.4, Percent Flicker≤5%@≤200Hz

Installation

Mounting:
3M Tape, aluminum profile

Construction

Reel Length:
32 ft

Max Run Length:
32 ft

PCB Width:
8mm

Light Source:
COB LED White

Material Construction:
Super-flexible bending, ultra-thin appearance, premium wall structure, & thick copper to ensure consistancy in voltage and brightness.

Bendable:
Top bend

Light Effect:
Continuous band light output with no pixelated hot spots

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Compliance

Listings:
UL2108

Environment:
Suitable for use indoors in dry and damp environments.

IP Rating:
IP20

Certification Model Number:
TICYN

California Title 20 Compliant:
No

California Title 24 JA8 Compliant:
Can be used to conform with the requirements of California Title 24 Part 6.

California Energy Commission (CEC) Status:
Lawful for Sales in California

NSF Listed:
No

NEC Compliant:
Suitable for use in closets when used in an enclosed extrusion based on NFPA 70, NEC section 410.16 (A)(1) and 410.16 (C)(1)

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
No

Other

Field Wiring Accessories:
TIJ2
2-Pin indoor connector kits

TIJ2L
2-Pin indoor L-shape connector kits

Mounting Accessories:
TAP12
12mm wide aluminum channel kits

TAP16TL
Trimless 16mm inner wide recessed aluminum profile

Compatible Drivers:
TID-60
Indoor 60W driver

TID-96
Indoor 96W driver

TOD-96
Outdoor 96W driver

TID/B
J-box for TID Drivers

TOD-96x2
96Wx2 outdoor driver

TOD-96x3
96Wx3 outdoor driver

5-Year Limited Warranty:
The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

TAP16C
Corner 16mm wide aluminum profile

Ordering Matrix

Family	Length	Lumen Output	CRI/Color Temp	Input Voltage	IP Rating	Controls
TIC			YN			
	Blank = 32 ft **L =** 100 ft	**Blank =** Standard	**YY =** 90 CRI, 2700K **Y =** 90 CRI, 3000K **YN =** 90 CRI, 3500K **N =** 90 CRI, 4000K **CW =** 90 CRI, 5000K	**Blank =** 24 DC	**Blank =** IP20, Indoor	**Blank =** None

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice