
TM-4T600NRG/480



Color: Roadway gray

Weight: 60.3 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	N/A
208V	N/A
240V	N/A
277V	N/A
Input Watts	139.7-577W

LED Info

Watts	600/540/480/420/360/300/240/150W
Color Temp	4000K
Color Accuracy	73-74 CRI
L70 Lifespan	100,000 Hours
Lumens	23768-83632 lm
Efficacy	144.9-170.1 lm/W

Technical Specifications

Field Adjustability

Field Adjustable:
Field Adjustable Light Output:
600/540/480/420/360/300/240/150W (factory default 600W)
Rotatable Optics: 165° L/R) and 0-5° tilt

Compliance

UL Listed:
Suitable for wet locations

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

IP Rating:
Ingress protection rating of IP66 for dust and water

DLC Listed:
This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at designlights.org to confirm the qualification status of a specific SKU prior to specification or purchase.

Optical

IES Classification:
The Type IV distribution is especially suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. It produces a semicircular distribution with essentially the same candlepower at lateral angles from 90° to 270°.

BUG Rating:
B5 U0 G5

LED Characteristics

LEDs:
Long-life, high-efficacy, surface-mount LEDs

Color Stability:
LED color temperature is warrantied to Shift no more than 200K in color temperature over a 5-year period

Performance

Lifespan:
100,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations

Electrical

Driver:
Constant Current, Class 1, Class P, 480V, 50/60 Hz:
600W: 120V: 1.5A
540W: 120V: 1.2A
480W: 120V: 1.1A
420W: 120V: 1.0A
360W: 120V: 0.8A
300W: 120V: 0.7A
240W: 120V: 0.6A
150W: 120V: 0.4A

Dimming Driver:
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

Aux Power Supply:
Yes

Dim to Off:
Yes

Surge Protection:
20 kV

7-Pin Receptacle with Shorting Cap:
ANSI C136.41 7-pin receptacle, compatible with wireless control systems

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Construction

Cold Weather Starting:
The minimum starting temperature is -40°F (-40°C)

Maximum Ambient Temperature:
Suitable for use in up to 113°F (45°C)

IK Rating:
IK08 Protected against 5 joules of impact. Equivalent to the impact of a 3.75 lbs. (1.7kg) mass dropped from 11.8" (300mm) above the impacted surface.

Effective Projected Area (EPA):
1.64 ft^2

Housing:
Die-cast aluminum

Lens:
High-transmittance polystyrene

Gaskets:
High-temperature silicone

Vibration Rating:
3G vibration rating per ANSI C136.31

Tilt Increment:
Rotates in 1 degree increments

Finish:
Formulated for high durability and long-lasting color

Installation

Mounting:
Fits existing infrastructure: Mounts to 1-5/8" to 2-3/8" pipe arms on 50 to 130 ft poles


Other


5-Year Limited Warranty:
The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

TM-4T600NRG/480

Dimensions





Features

- 100,000-Hour LED lifespan
- DLC Premium
- 0-10V Dimming
- IP66 Rating protects against dust & water ingress
- Industry-leading 3G vibration rating per ANSI C136.31
- 5-Year, limited warranty

Ordering Matrix

Family		Distribution	Wattage	Mounting	Color Temp	Finish	Driver	Controls
TM	–	4T	600		N	RG	/480	
		1T = Type I **2T =** Type II **3T =** Type III **4T =** Type IV **5T =** Type V	**600 =** 600/540/480/420/360/300/240/150W **900 =** 900/810/720/630/540/450/360/225W	**Blank =** Adjustable Pole Mount	**Blank =** 5000K **N =** 4000K	**Blank =** Bronze **RG =** Roadway Gray	**Blank =** 120-277V, 0-10V Dimming **/480 =** 200-480V, 0-10V Dimming	**Blank =** 7-Pin Receptacle with Shorting Cap

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice