TOSLY



Weight: 4.0 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Voltage, Class 2
120V	N/A
208V	N/A
240V	N/A
277V	N/A
Input Watts	2.5 W/ftW

LED Info

Watts	2.5W/ftW
Color Temp	N/A
Color Accuracy	N/A
L70 Lifespan	50,000 Hours
Lumens	260lm/ft lm
Efficacy	105

Technical Specifications

Performance

Description:
FLEXTAPE is a bendable, outdoor LED tape that provides energy-efficient lighting for both indoor and outdoor applications.

Input Wattage:
2.5W/ft

Lumens/Foot:
263 lm/ft

Efficacy:
105lm/W

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

LED Characteristics

Chip Density:
38 LED/ft

Beam Angle:
120°

Color Temperature:
3000K

Color Accuracy (CRI):
90 CRI

R9 Value:
High color performance with R9 greater than 60

Color Consistency:
<3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Field Cuttable Increment:
Cuttable every 2"

Electrical

Input Voltage:
DC24V

Operating Temperature:
-20°C to 45°C (-4°F to 113°F)

Storage Temperature:
-4°F (-20°C) to 140°F(60°C)

Installation

Mounting:
3M Tape, aluminum profile, silicone clips

Construction

Reel Length:
100 ft

Max Run Length:
32 ft

PCB Width:
8mm

Light Source:
SMD 2835

Material Construction:
Weather-reisistant, high-grade silicone cover with super-flexible bending .

Bendable:
Top bend

Light Effect:
Soft linear lighting performance

Compliance

Listings:
UL2108

Environment:
Suitable for use indoors and outdoors in dry, damp, or wet environments.

IP Rating:
IP67 Extrusion

IC Rated:
No

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Air Tight:
No

Energy Star Approved:
No

DLC NLC Listed:
No

DLC Listed:
No

Certification Model Number:
TOSLY

California Title 20 Compliant:
No

California Title 24 JA8 Compliant:
Meets certification standards

California Energy Commission (CEC) Status:
Lawful for Sales in California

NSF Listed:
No

NEC Compliant:
Suitable for use in closets when used in an enclosed extrusion based on NFPA 70, NEC section 410.16 (A)(1) and 410.16 (C)(1)

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
No

Other

Field Wiring Accessories:
TPF2
2-Pin power feed kit

TSG
10ml Silicone glue

TOJ2
2-Pin outdoor connector kit

TOJ2L
2-Pin outdoor L-shape connector kit

Mounting Accessories:
TSC2
Silicone mounting clips

TAP15
15.5mm wide aluminum channel kits

TAP16TL
Trimless 16mm inner wide recessed aluminum profile

TAP16C
Corner 16mm wide aluminum profile

Compatible Drivers:
TID-60
Indoor 60W driver

TID-96
Indoor 96W driver

TID/B
J-box for TID driver

TOD-96
Outdoor 96W driver

TOD-96x2
96Wx2 outdoor driver

TOD-96x3
96Wx3 outdoor driver

5-Year Limited Warranty:
The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Ordering Matrix

Family	Length	Lumen Output	CRI/Color Temp	Input Voltage	IP Rating	Controls
TOS	L		Y			
	Blank = 32 ft **L =** 100 ft	**Blank =** Standard	**YN =** 90 CRI, 3500K **N =** 90 CRI, 4000K **CW =** 90 CRI, 5000K **Y =** 90 CRI, 3000K **YY =** 90 CRI, 2700K	**Blank =** 24 DC	**Blank =** IP67, Outdoor	**Blank =** None

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice