VC200W

$\mathsf{D}\mathsf{A}\mathsf{P}$



Weight: 3

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, noncombustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

Construction

Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

No Guard Supplied:

Electrical

Maximum Watts: 150W

Colored Globe Maximum Watts: 100W

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Watts

Base

ANSI

Hours

Efficacy

Shape/Size

Lamp Lumens N/A

150W

N/A

N/A

N/A

N/A

N/A

Project: Prepared By:		Туре:
		Date:
Lamp Inf	o A19	Ballast Info Type N/A

120V

208V

240V

277V

Input Watts N/A

N/A

N/A

N/A

N/A

VC200W

RAB