

Date:

### Lamp Info

|             |      |
|-------------|------|
| Type        | A19  |
| Watts       | 150W |
| Shape/Size  | N/A  |
| Base        | N/A  |
| ANSI        | N/A  |
| Hours       | N/A  |
| Lamp Lumens | N/A  |
| Efficacy    | N/A  |

### Ballast Info

|             |     |
|-------------|-----|
| Type        | N/A |
| 120V        | N/A |
| 208V        | N/A |
| 240V        | N/A |
| 277V        | N/A |
| Input Watts | N/A |

Pendant mount, die cast aluminum construction. Medium base socket, 1/2" or 3/4" NPS pendant thread and a variety of globes. incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied.

Color: Natural

Weight: 1.2 lbs

## Technical Specifications

## Compliance

**UL Listed:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

## Construction

**Globes:**

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

**No Guard or Globe Supplied:**

**Hub Size:**

3/4" Tapped

## Other

### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

