

NO IMAGE AVAILABLE

Pendant mount, die cast aluminum construction. Medium base socket, 1/2" or 3/4" NPS pendant thread and a variety of globes. Incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied.

Color: White

Weight: 3.3 lbs

Project:	Type:
Prepared By:	Date:

Lamp Info	Ballast Info
Type A19	Type N/A
Watts 200W	120V N/A
Shape/Size N/A	208V N/A
Base N/A	240V N/A
ANSI N/A	277V N/A
Hours N/A	Input Watts N/A
Lamp Lumens N/A	
Efficacy N/A	

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

Construction

Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

No Guard Supplied:

Electrical

Maximum Watts:

200W

Colored Globe Maximum Watts:

150W

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Need help? Tech help line: (888) 722-1000 Email: sales@rablighting.com Website: www.rablighting.com

Copyright © 2025 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Page 1 of 2

