
VX100DGS-3/4



Box mount, die cast aluminum with built-in junction box and sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. incandescent A21 for 100 Series, PS25 for 200 Series. Lamp not supplied.

Color: Silver

Weight: 2.4 lbs

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, noncombustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

Construction

Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

Die Cast Guard:

Supplied with one piece silver gray die cast guard with set screw

Hub Size:

3/4" Tapped

Electrical

Maximum Watts: 150W

Colored Globe Maximum Watts: 100W

Input Voltage: 120V

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.


Project:		Туре:		
Prepa	Prepared By:		Date:	
Lamp Inf	ö	Ballast I	nfo	
Туре	A21	Туре	N/A	
Watts	150W	120V	N/A	

	Shape/Size	N/A	208V	N/A
•	Base	N/A	240V	N/A
it lamp	ANSI	N/A	277V	N/A
	Hours	N/A	Input Watts	N/A
	Lamp Lumens	N/A		
	Efficacy	N/A		

VX100DGS-3/4







Features

All stainless steel hardware

Close-up plugs allow Phillips or slotted screwdrivers for easy installation

Junction box with sturdy mounting lugs

UL Listed for use with 90°C supply wiring OK for use in dwellings and wet locations

High temperature silicone internal gaskets

Premium porcelain socket with 150C 8" long leads