

	rioject.	туре.
NO IMAGE AVAILABLE	Prepared By:	Date:
		<b>5</b> H 6
	Lamp Info	Ballast Info

Project:

Box mount, die cast aluminum with built-in junction box and sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. incandescent lamp A21 for 100 Series, PS25 for 200 Series. Lamp not supplied.

Color White

Neight 42 lbs

Lamp Info		Ballast Info	
Туре	PS25	Туре	N/A
Watts	300W	120V	N/A
Shape/Size	N/A	208V	N/A
Base	N/A	240V	N/A
ANSI	N/A	277V	N/A
Hours	N/A	Input Watts	N/A
Lamp Lumens	N/A		
Efficacy	N/A		

Type

# **Technical Specifications**

## Compliance

#### **UL Listed:**

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, noncombustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

# Construction

### Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

### Wire Clamp Guard:

8 GA steel wire white powder coated

#### **Electrical**

### **Maximum Watts:**

300W

## **Colored Globe Maximum Watts:**

200W

## Input Voltage:

120V

#### Other

#### **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

**VX200GW** 

