
RAB



Color: Natural

Weight: 1.7 lbs

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, noncombustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

Construction

Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

No Guard or Globe Supplied:

Hub Size: 3/4" Tapped

Electrical

Input Voltage: 120V

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Lamp Lumens N/A

N/A

Efficacy

Project: Prepared By:			Туре:		
		Date:			
Lamp Info		Ва	Ballast Info		
Туре	A21	T	ype	N/A	
Watts	300W	1.	20V	N/A	
Shape/Size	N/A	2	08V	N/A	
Base	N/A	2	40V	N/A	
ANSI	N/A	2	77V	N/A	
Hours	Hours N/A		Input Watts N/A		

VX2-3/4

RAB