



Handheld wireless configuration tool enables contractors and end-users to customize sensor control settings for PORTO fixtures with the simple click of a button - no ladders required.

Color: Bronze

Weight: 0.0 lbs

Project:	Type:
Prepared By:	Date:

**Technical Specifications**

**Sensor Specifications**

**Power Consumption:**

1W

**0-10V Sinking Current:**

50mA

**Adjustable High and Low Modes:**

High: 0-10V; Low: off, 0-9.8V

**Adjustable Time Delay:**

Amount of time in high mode with no motion before switching to low mode: 5 min., 1 -30 min.

**Adjustable Cut Off Delay:**

Time in which the fixture will remain on low mode with no motion before turning off and waiting for new motion to turn on: None, 1 -60 min., 1 -5 hrs.

**Adjustable Sensitivity:**

None, low, medium, maximum

**Adjustable Setpoint:**

None, 1 to 250 fc, auto

**Operating Temperature:**

-40°F to 167°F (-40°C to +75°C)

**Operating Humidity:**

20% to 90% noncondensing

**Relay Life Rating:**

200,000 cycles (120/277VAC), 50,000 cycles (230VAC)

**IP Rating:**

Ingress protection rating of IP66 for dust and water

**UL Listed:**

Suitable for Wet Locations as factory installed

**Other**

**Compatible Products:**

- [AEROBAY with /PIR](#)
- [RAIL with /PIR](#)
- [VANLED with /WS or /WS2](#)
- [IVEPARK with /WS or /WS2](#)
- [PORTO with /WS or /WS2](#)
- [IVELOT with /WS, /WS2, or /WS4](#)
- [ALED with /WS2, or /WS4](#)

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

